

# B730 | Backhoe Loaders

## Specifications

### Engine

Make / Model	Perkins / 1104C-44T
Compliance	EU Stage II and EPA Tier 2
Aspiration	Turbocharged
Number of cylinders	4.0
Displacement	4.40 L
Rated gross power (ISO 14396)	74.5 kW
Rated gross power (ISO 14396)	100.0 HP
Rated speed	2200.0 RPM
Maximum torque @1350 RPM	408.0 Nm
Fuel	Diesel
Cooling	Water

### Electrical System

Battery	12 V 120 Ah
Starter	3.2 kW

### Transmission

Make / Model	ZF
Type	Powershift
Max travel speed 1st forward/reverse	6.5/7.0 km/h
Max travel speed 2nd forward/reverse	11.0/12.0 km/h
Max travel speed 3rd forward/reverse	26.0/30.0 km/h
Max travel speed 4th forward/reverse	40.0/0.0 km/h

### Front Axle

Type	4WD
Limited slip	Standard
Oscillation	20.0°

### Rear Axle

Make	ZF
Differential lock	Standard

### Hydraulic System

System type	Open centre
Pump	Tandem gear pump
Flow	90.0 + 64.0 L/min
System pressure	220.00 bar
Controls, backhoe	Mechanical levers
Controls, loader	Mechanical lever

### Steering

Type	2WS
Turning circle (unbraked), outside front tyres	9500.0 mm
Turning circle (unbraked), outside loader bucket	12320.0 mm

### Brakes

Service type	Hydraulic wet multi disc, dual pedal braking
Parking type	Mechanical control on rear axle

### Operating Weights

Base machine	7800 kg
--------------	---------


### Tyres

4WD front	12.5-18
Rear	16.9-28

### Standard Features


ROPS/FOPS Enclosed cab	Exterior mirrors
Mechanical suspension seat with seat belt	Radio/CD player
Arm rest	Rotating beacon
Sunvisor	Horn
Floor mat	Reverse alarm
Tilted steering column	Heater
Steering wheel knob	Rear windscreen heater
Tinted front windscreen and wiper	600 mm backhoe bucket
Tinted rear windscreen and wiper	Fully equipped dashboards
6 work lights (2 front, 4 rear)	General purpose loader bucket
Side storage	

### Dimensions



(A)	5950.0 mm	(F)	3900.0 mm
(B)	2180.0 mm	(G)	2280.0 mm
(C)	1300.0 mm	(H)	2280.0 mm
(D)	380.0 mm	(J)	1770.0 mm
(E)	2900.0 mm	(K)	1895.0 mm

### Working range



(Retracted/Extended)			
(A)	4600/5800 mm	(J)	59.2°
(B)	7000/8100 mm	(K)	2810.0 mm
(C)	5700/6800 mm	(L)	3280.0 mm
(D)	5600/6450 mm	(M)	3520.0 mm
(E)	3850/4700 mm	(N)	1070.0 mm
(F)	1800/2650 mm	(O)	620.0 mm
(G)	200.4/200.4 °	(P)	115.0 mm
(H)	4750/5550 mm	(R)	45.0°
(I)	1220.0 mm		

### Loader Performance

Bucket capacity, GP	1.10 m <sup>3</sup>
Breakout force, bucket	81.50 kN
Breakout force, arm	60.50 kN
Rated operating capacity at max height	3500 kg

### Backhoe Performance

Bucket capacity	0.20 m <sup>3</sup>
Bucket tearout	59.10 kN
Dipper tearout retracted	31.80 kN

### Options

Air conditioning	Ride Control
ROPS/FOPS Canopy	

### Optional Attachments

Backhoe	
Hammer piping	
Different sizes of backhoe buckets	
Hydraulic hammer	
Extendable boom	
Loader	
6 in 1 loader bucket	
Pallet forks	