



**Club Car**®

6 PASSENGER  
**ONWARD**®

MORE ROOM. MORE PASSENGERS.

*More Fun!*

Meet the Onward 6 Passenger, the only 6 passenger vehicle that meets all ANSI Personal Transportation Vehicle safety and performance standards. It's everything you already love about Onward - but more. And, with the warranty, backing & support you expect from Club Car, your family can focus on what really matters

**CRAFTED FOR PEACE OF MIND.**

4 wheel brake performance that is crafted and engineered for optimal stopping power



Front row under-seat storage tray with multiple compartments

Available in all Onward standard colors, options, upgrades and accessories

The extended body aesthetic parts have been designed for a fully integrated and sleek look.





## CRAFTED FOR COMFORT.

- Long, one-piece canopy design that covers the rear facing passengers
- Ergonomic grab handles for second row passengers and dual cup holders positioned for easy reach
- Front row seat pod purposely engineered to provide ample leg room for second row passengers
- Enhanced suspension system for improved handling and performance

DIMENSIONS	6 PASSENGER NON- LIFTED		6 PASSENGER LIFTED	
	GAS	AC ELECTRIC	GAS	AC ELECTRIC
Dimensions	143 in (363.2 cm)	143 in (363.2 cm)	148 in (375.9 cm)	148 in (375.9 cm)
Overall Width	44.5 in (112.9 cm)	44.5 in (112.9 cm)	51.3 in (130.5 cm)	51.3 in (130.5 cm)
Topped Height	73.5 in (186.7 cm)	73.5 in (186.7 cm)	88.5 in (224.8 cm)	88.5 in (224.8 cm)
Untopped Height	49.25 in (125.1 cm)	49.25 in (125.1 cm)	55.1 in (140 cm)	55.1 in (140 cm)
Wheel Base	101.1 in (256.8 cm)	101.1 in (256.8 cm)	103.2 in (262.2 cm)	103.2 in (262.2 cm)
Front Wheel Track	37.1 in (94.3 cm)	37.1 in (94.3 cm)	40.4 in (102.5 cm)	40.4 in (102.5 cm)
Rear Wheel Track	37 in (93.9 cm)	37 in (93.9 cm)	40.25 in (102.2 cm)	40.25 in (102.2 cm)
Ground Clearance	4.5 in (11.5 cm)	4.5 in (11.5 cm)	7.1 in (18.1 cm)	7.1 in (18.1 cm)
POWER				
Power Source	Gas	48V AC	Gas	48V AC
Motor Type	429 cc Kohler, Overhead Valve (OHV) with EFI	30V AC motor	429 cc Kohler, Overhead Valve (OHV) with EFI	30V AC motor
Horse Power	14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	4.7 hp	14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	4.7 hp
Batteries (qty/type)	One 12-volt	(6) 8V Flooded Lead Acid	One 12-volt	(6) 8V Flooded Lead Acid
Key or Pedal Start	Pedal	Pedal	Pedal	Pedal
Battery Charger		48V Shelf or On-board		48V Shelf or On-board
	N/A	Option	N/A	Option
Speed Controller	N/A	375 Amp AC	N/A	375 Amp AC
Drivetrain		Motor Shaft Direct Drive		Motor Shaft Direct Drive
Transaxle				
Gear Selection	Center Body Mounted FNR	Center Body Mounted FNR	Center Body Mounted FNR	Center Body Mounted FNR
Rear Axel Ratio	Forward 11.47:1 Reverse 15.63:1	14.85:1	"Forward 11.47:1 Reverse 15.63:1"	14.85:1
PERFORMANCE				
Seating Capacity	6	6	6	6
Dry Weight(w/o Batteries)	951		1071	
Curb Weight	980	1284	1101	1402
Vehicle Load Capacity	1200	1200	1200	1200
Outside Clearance Circle	151 in (383.5 cm)	151 in (383.5 cm)	171.9 in (436.6 cm)	171.9 in (436.6 cm)
High Speed (Level Ground)	18 +/-1 mph	18 +/-1 mph	18 +/-1 mph	18 +/-1 mph
Low Speed (Level Ground)	n/a	n/a	n/a	n/a
STEERING SUSPENSION				
Steering	SportDrive™ – Self-compensating double reduction helical rack & pinion	SportDrive™ – Self-compensating double reduction helical rack & pinion	SportDrive™ – Self-compensating double reduction helical rack & pinion	SportDrive™ – Self-compensating double reduction helical rack & pinion
Suspension (front & rear)	Front: Independent A-arms with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers	Front: Independent A-arms with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers	Front: Independent wide track Double A-arm with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers	Front: Independent wide track Double A-arm with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers
Brakes	Self-adjusting, four wheel mechanical drum	Self-adjusting, four wheel mechanical drum	Self-adjusting, four wheel mechanical drum	Self-adjusting, four wheel mechanical drum
Parking Brake	Foot actuated, 3-position	Foot actuated, 3-position	Foot actuated, 3-position	Foot actuated, 3-position
Tires	205 x 55 - 10 Loadstar Tubeless	205 x 55 - 10 Loadstar Tubeless	22 x 10 - 10 Kraken Tubeless	22 x 10 - 10 Kraken Tubeless
BODY & CHASSIS				
Frame	AlumiCore™ – Ladder-style aluminum box beam			
Body & Finish	Front: Painted TPO   Center: Painted High Impact ABS   Rear: Painted Surlyn			
Available Body Colors	Metallic Pearl Blue, Metallic Jade Green, Metallic Tuxedo Black, Metallic Platinum, Metallic Candy Apple Red, Metallic Glacier, Metallic Beige, Metallic Ocean Teal			
Available Seat Colors	Standard Beige, Standard White, Standard Black, Premium Light Beige, Premium Camello, Premium Off White, Premium Black, Premium Black/Gray, Premium Gray			